brother
at your side

PT-9700PC | TZ-Tape

3 YEAR WARRANTY

PC connectable Desktop Labelling machine

Copy

Professional labelling machine
There's no messing around with the PT-9700PC. This high speed, high quality professional label printer gives you wide, durable labels in an instant. Perfect for where many labels are required quickly, such as manufacturing, event management, filing systems and asset management.

Catalogue Spec

- Print Tested to the extreme labels up to 36mm
- Print high quality durable barcode labels in an instant
- Advanced cutter – capable of printing a strip of labels that is half-cut and ready to peel easily
- Fast Print Speeds of up to 80mm per second
- Prints 6, 9, 12, 18, 24 & 36mm labels
- Includes 36mm black on white HG tape (8m)

What's in the Box

- 36mm black on white HG tape
- AC Adapter
- USB cable
- CD-ROM
- Users guide

PT-9700PC

Colour: Light Grey and Pearl White

Tape widths: Machine accepts current range of HG & TZ Tapes:
- 3.5mm to 36mm (TZ Tapes)
- *12mm to 36mm (HG Tapes)

Tape inclusion:
HG-261 36mm Black on white (8 Metre length) tape

Keyboard: N/A

In the Box:

PT-9700PC Labelling machine
36mm HG-261 black on white label cassette
AC adaptor
USB cable
CD-ROM containing software, drivers and user guide

Hardware

PRINTING	PT-9700PC
Dimensions	116mm(W) x 192.7mm(D) x 140mm(H)
Design	Cube
Weight	1.57kg
Housing Color	Light Gray & Pearl White
Keyboard	Not available
Number of Keys	2(Power On/Off, Feed and Cut)
Tape Cutter	Auto Full Cutter, Auto Half Cutter (Laminated tape only)
Power	AC adaptor (AD9100ES) (Enclosed)
Display	Not available
Panel LED lamp	Red For Error status Green For Ready status
USB A lamp	None
LAN LED lamp	None
Attachments	CD-ROM [P-touch Editor 5.0 for Windows, P-touch Editor 5.0 for Mac, Printer Driver, Software User's Guide, P-touch Template tools, ESC/P tools] User's guide HG tape(36mm Black on White Laminated Tape)

Tape Cartridge	*TZ Tape, HG Tape*
Tape width variations	*TZ 3.5-36mm, HG Tape 6-36*
Print Method	*Thermal transfer*
Max. Print Height	*27.1mm*
Print Speed(tentative)	*Maximum. 20mm / sec (For TZ/AL tape)* *Maximum. 52mm / sec (For high-speed mode of HG tape only)* *Maximum. 80mm / sec (For high-speed draft mode of HG tape only)*
Print Head	*360 dpi/384 dots*
Print resolution	*360dpi(TZ / AL tape)* *360dpi x 720dpi(For high resolution mode of HG tape only)* *360dpi x 180dpi(For high speed mode of HG tape only)*
Cutter Sensor	*Yes*
Tape End Sensor	*Yes*
Cover Open Sensor	*Yes*
Tape sensor	*Yes*
USB Function Interface	*USB2.0 Full Speed*
RS-232C Interface	*Yes*
USB Host Interface	N/A
LAN Interface	*N/A*
ESC/P Printing	*Yes*
USB ID switching	*N/A*

Temperature	*10°C to 35°C*
Humidity	*20% to 80%*