


QL-1060N

DK Labels



Versatile and Easy to use thermal label



## Copy

### Catalogue Spec

- Network ready perfect for sharing
- Industrial – supports and prints most 1D and 2D barcode types
- Professional – built in automatic label cutter leaves a clean cut edge.
- Quick and effective - prints up to 69 labels per minute
- High quality 300 x 300dpi resolution print
- No Paper Jams, No Ink or Toner needed, No label wastage
- Easy peel labels
- Print continuous length or pre sized die cut labels
- Includes 62mm black on white continuous length tape (8m) and large shipping labels (40 labels)
- Prints 12mm – 102mm wide labels

### What's in the Box

- 62mm black on white continuous length tape
- Large shipping labels (40 labels)
- CD ROM
- Quick start guide
- USB Cable
- AC adapter
- DK roll guide

## Hardware

QL-1060N for EU	
<b>Dimensions</b>	170mm(W) x 220mm(D) x 147.5mm(H)
	6.7"(W) x 8.7"(D) x 5.8"(H)
<b>Weight</b>	1.73kg (without DK roll)
	3.8pounds (without DK roll)
<b>Housing Color</b>	Black
<b>Key Board</b>	No
<b>Number of Keys</b>	3 (On/Off, Feed, Cut)
<b>Cutter</b>	Durable Auto cutter (User unreplaceable)
<b>Auto Half Cutter</b>	No
<b>Power supply</b>	Internal S/W Power Supply
<b>LCD</b>	No
<b>LED</b>	1 (3 color - Green, Red, Orange)
<b>Print Method</b>	Thermal
<b>Attachments</b>	CD-ROM (P-touch Editor 5.0 for Windows, P-touch Address Book 1.1, P-touch Editor 5.0 for Mac, Printer Driver, User's Guide, P-touch Template tools, ESC/P tools)
	Setup & Operation Guide
	DK Rolls Line-up Guide
	Label Tray
	USB cable
	Warranty card
	DK-11241 (102mm x 152mm White Paper Labels) Starter roll (40 labels)
	DK-22205 (62mm Continuous Length Paper Tape) Starter roll (8 m)
	AC Power cord
	EEE insertion
	<b>Roll Type</b>
<b>Roll Width</b>	Max. Label width 102mm (4")
<b>Print Head</b>	300 dpi / 1296 dots
<b>Print Speed</b>	110 mm (4.3") / sec.
	69 standard address labels / min.
<b>Strap / Handle</b>	No
<b>Computer Interface</b>	USB, RS-232C, 10/100 BASE-TX Wired Ethernet
<b>LCD Mylar</b>	No
<b>Mylar Sticker</b>	No

## Software and Firmware

QL-1050 for EU	
<b>Printer Driver</b>	QL-1060N
<b>Label Editing Software</b>	Win: P-touch Editor ver. 5.0, P-touch Address Book ver. 1.1
	Mac: P-touch Editor ver. 5.0
<b>Maximum Print Width</b>	98.6mm (3.9") max.

<b>Printable Label Length</b>	25.4mm (1") - 3m (10') (USB)
	25.4mm (1") - 1m (3') (Serial)
<b>Number of Printing</b>	1 - 9999 (USB)
	1 - 99 (Serial)
<b>Bar Code</b>	Software side: CODE39, CODE128, EAN8, EAN13, EAN128, UPC-A, UPC-E, I-2/5(ITF), CODABAR, ISBN-2, ISBN-5, Laser Bar Code, POSTNET, QR code, MicroQR code, PDF417, Data Matrix, MaxiCode, Micro PDF 417, RSS-14, RSS-Limited, RSS Expanded
	Machine side: CODE39, CODE128, EAN8, EAN13, EAN128, UPC-A, UPC-E, I-2/5(ITF), CODABAR, QR code, MicroQR code, PDF417, Data Matrix, MaxiCode, Micro PDF 417, RSS-14, RSS-Limited, RSS Expanded
<b>Printer control command</b>	Raster mode
	ESC/P mode
	P-touch Template mode
<b>Template Transfer</b>	YES
<b>Memory for transferred data</b>	99 Templates or 2048KB
<b>Character code set</b>	Standard character code
	Windows-1252 Western Europe character code
	Windows-1250 Eastern Europe character code
<b>Built in Fonts</b>	Bitmap fonts: Helsinki, Brussels, Letter Gothic Bold, San Diego, Brougham
	Outline fonts: Helsinki, Brussels, Letter Gothic
<b>Built in Font size</b>	Bitmap fonts: 24 dots, 32 dots, 48 dots
	Outline fonts: 33 dots - 400 dots (22 sizes)
<b>Built in Font style</b>	Outline, Shadow, Outline+Shadow, Italic, Underline, Bold, Vertical
<b>Built in Font widths (ESC/P printing only)</b>	x2 (Width), x2 (Height), x1/2 (Width)
<b>Add-in for Microsoft</b>	Word, Outlook, Excel
<b>Database file compatibility</b>	csv, txt, mdb, xls
<b>Special printing</b>	Mirror printing
	Vertical printing
	Rotated Printing
<b>Time &amp; Date Stamp</b>	PC Generated
<b>Number of Preset Templates</b>	No
<b>Number of Date formats</b>	No
<b>Number of Time formats</b>	No
<b>Number of Preset messages</b>	No