

QL-650

DK Labels



Versatile and Easy to use thermal label



Copy

Catalogue Spec

- Incorporates built-in clock and control panel – use with or without a PC
- Professional – built in automatic label cutter leaves a clean cut edge.
- Quick and effective - prints up to 56 labels per minute
- No Paper Jams, No Ink or Toner needed, No label wastage
- Easy peel labels
- Print continuous length or pre sized die cut labels
- Includes 62mm black on white continuous length tape (8m) and 24mm round labels (200 labels)
- Prints 12mm – 62mm wide labels

What's in the Box

- 62mm black on white continuous length tape
- 24mm Round labels (200 labels)
- CD ROM
- Setup and operation guide
- USB Cable
- AC adapter
- DK roll guide
- Cleaning sheet

Hardware

QL-650TD for EU	
Dimensions	146mm(W) x 196mm(D) x 152mm(H) 5.7"(W) x 7.6"(D) x 5.9"(H)
Weight	1.3kg (without DK roll) 2.8pounds (without DK roll)
Housing Color	Black
Key Board	No
Number of Keys	9 (On/Off, Print, Feed, Cut, Menu, Cancel, OK, Up arrow and Down arrow)
Cutter	Auto cutter (User replaceable)
Auto Half Cutter	No
Power supply	Internal S/W Power Supply
LCD	Yes
LED	1 (1 color - Green)
Print Method	Thermal
Attachments	CD-ROM (P-touch Editor 4.2 for Windows, P-touch Address Book 1.0, P-touch Editor 3.2 for Mac, Printer Driver, Software User's Guide, ESC/P tools, Adobe Acrobat Reader 5.1) Setup and Operation Guide DK Rolls Line-up Guide Label Tray USB cable Warranty card DK-11218 (24mm Round Paper Labels) Starter roll (250 labels) DK-22205 (62mm Continuous Length Paper Tape) Starter roll (8 m) AC Power cord EEE insertion Cleaning sheet Lithium battely Unpacking instruction Insertion QL-650TD
Roll Type	DK rolls (DK Die-cut Labels / DK Continuous Length Tape)
Roll Width	Max. Label width 62mm (2.4")
Print Head	300 dpi / 720 dots
Print Speed	90 mm (3.5") / sec. 56 standard adress labels / min.
Strap / Handle	No
Computer Interface	USB, Serial (RS-232C)
LCD Mylar	No
Mylar Sticker	No

Software and

Firmware

QL-650TD for EU	
Printer Driver	QL-650TD
Label Editing Software	Win: P-touch Editor ver. 4.2, P-touch Address Book ver. 1.0
	Mac: P-touch Editor ver. 3.2
Maximum Print Width	59mm (2.3") max.
Printable Label Length	25.4mm (1") - 1m (3')
Number of Printing	1 - 9999 (USB)
	1 - 99 (Serial)
	1 - 999 (StandAlone)
Bar Code	Software side: CODE39, CODE128, EAN8, EAN13, EAN128, UPC-A, UPC-E, I-2/5(ITF), CODABAR, ISBN-2, ISBN-5, Laser Barcode, POSTNET, QR code, MicroQR code, PDF417, Data Matrix
	Machine side(*1): CODE39, CODE128, EAN8, EAN13, EAN128, UPC-A, UPC-E, I-2/5(ITF), CODABAR, QR code, MicroQR code, PDF417
Printer control command	Raster mode
	ESC/P mode
Template Transfer	YES
Memory for transferred data	36 Templates or 288KB
Character code set	Standard character code
	Windows-1252 Western Europe character code
	Windows-1250 Eastern Europe character code
Built in Fonts	Bitmap fonts: Helsinki, Brussels, Letter Gothic Bold, San Diego, Brougham
Built in Font size	Bitmap fonts: 24 dots, 32 dots, 48 dots (24, 32, 48, 64, 96 dots)
Built in Font style	Outline, Shadow, Outline+Shadow, Italic, Underline, Bold, Vertical
Built in Font widths (ESC/P printing only)	x2 (Width), x2 (Height), x1/2 (Width)
Add-in for Microsoft	Word, Outlook, Excel
Database file compatibility	csv, txt, mdb, xls
Special printing	Mirror printing
	Vertical printing
	Rotated Printing
Time & Date Stamp	Stand alone / PC Generated
Number of Preset Templates	8
Number of Date formats	12 (14 for Germany, 10 for French)
Number of Time formats	3
Number of Preset messages	10
notetext	(*1) &trademark_denso_ql1_en; &trademark_ainix_ql1_en;